aetena 39 Suprabam 17 Suprabam 18 Suprabam

LED / Focus configuration:	1 CREE Power Chip / Sliding Hyperfocus™ Lens
Case Material / Surface Treatment:	Anodized and urethane coating, High Strength Aluminium
Case Color:	Black
Switch:	Quality Tested Silicone Switch With Touch Function - Switch At Rear
Dimensions:	L: 139.3mm, ø: 39mm
Weight incl. battery:	212g
Ingress Protection Rating:	Splash Waterproof IPx4
Temperature:	-20°C to +50°C
Built in Controller:	YES, 5-step controller by press or touch
Standard Power Source:	4 x AAA Alkaline
Compatible with rechargeable cells:	YES, with AA NiMh 1.2 V
Beam / Distance:	Variable from Spot to Floodlight / 220 Meters
Luminous Flux:	Max: 350 lm / High: 200 lm / Medium: 50 lm / Low: 15 lm / Strobe 10 Hz
Lighting Time:	Max: 1h / High: 1h 30min / Medium: 11h / Low: 75h
Accessories included:	Pro. Quality Pouch with magnetic lock and Press Stud
Customs Tariff Number:	8513 1000
Packaging:	Presentation tube
Single Box Content / Size / Weight:	1 pcs, height/diameter, 18 x 9,7 cm / 343 g
Master Box Content / Size / Weight	: 32 pcs, 38 x 40 x 44 cm / 11.2 kg
Order's Adress:	info@suprabeam.com

Barcode and part number, varies by language, contact Suprabeam for information.

